



ALL MATERIAL ARE RoHS AND CALIFORNIA PROP.65 COMPLIANT




CUSTOMER'S APPROVAL: _____ DATE: _____
FIRST ARTICLE SAMPLE REQUIRED: ☐ YES, ☐ NO.



18 CONTACTS ONLY
W/OUT PIN 4,5,12,13,20,21



PINOUT CONFIGURATION



THIS WIRE SPEC.CAN ONLY SUPPORTS THE ELECTRICAL PERFORMANCE UPTO 5 METERS FOR LONGER LENGTH, PLEASE USE TTL'S PATENTED SLAC™ WIRE DESIGN.
NOTE:

1. THIS ITEM CONTAINS PAT. US 6,287,148 B1 RF-BLOK™ SHIELDING DESIGN.
2. WIRE MARKING:

(TTL)® E193793 AWM 20276 80°C 30V VW-1 TOTAL TECHNOLOGIES. LTD.® DVI SINGLE LINK DIGITAL.



P/N	L(mm)
AK3739	1000
AK3740	2000
AK3741	3000
AK3742	5000

UNITS:mm

ITEM	DESCRIPTION	QTY.	UNIT
1	HDMI TYPE A 19PIN CONNECTOR,MALE W/GOLD PLATED PINS UL94V-0	1	PCS
2	DVI MALE CONNECTOR W/18 CONTACTS ONLY(18+1)	1	PCS
3	BLACK MOLDED PVC HOOD	1	PCS
4	PAT. US 6,287,148 B1 RF-BLOK™SHIELDING METAL CAN	1	PCS
5	BLACK #4/40 THUMBSCREW	2	PCS
6	(100 Ω SHIELDED TWIN PAIRS)X4+5C WIRE;AL-FOIL+ 85% BRAID ; BLACK PVC JACKET.	L	mm.
7	BLACK MOLDED PVC HOOD	1	PCS

REVISED DETAILS

REV.	DESCRIPTION	DATE	REVISED BY
A	CHANGE DVI COLOR TO BLACK	JUN.06.30	X.X.WANG
B	CHANGE HDMI SPEC	MAR.04.09	Q.F.WANG
C	ADD SIZE 1M(AK3739)	2013.05.29	Z.Q.KAGN

Part number:	Revision:
AK37xx	C
RFQ number: 65587	Drawing #: 65587-1
Drawn by: Y.X.SI	Scale: None
Checked by:	Date: 06/22/2004

